



VersaFlex Incorporated
87 Shawnee Avenue
Kansas City, KS 66105
(913) 321-9000
(913) 321-1490 (fax)

Product Data Sheet

Dzolv Solvent/Cleaner

Product Description- *VersaFlex Dzolv* is an environmentally friendly, water soluble, dibasic ester based solvent containing no aromatics or petroleum distillates. **Dzolv** is designed to provide maximum cleaning effectiveness while incorporating a high flash point and low toxicity. **Dzolv** acts to replace typical industrial solvents such as chlorinated hydrocarbons (methylene chloride, carbon tetrachloride, and 1,1,1-trichloroethane) ketones (acetone, methyl ethyl ketone) and aromatic solvents (xylene, toluene, and naphthalene).

Uses- **Dzolv** solvent/cleaner is designed to break down uncured polyurea, polyurethane, epoxies, and polyester resins.

Effective with-

- Grease
- Oil
- Inks
- Waxes
- Rubber Residues
- Lacquers
- Latex Paint
- Oil Based Paint

Advantages-

Not R.C.R.A. or DOT regulated. **Dzolv's** low toxicity and water solubility allow safe wash down and easy disposal through drains into sanitary systems.

- No VOC's
- Dilutes with Water
- Non Toxic
- Easy to Apply
- Non-flammable
- Flash Point > 200° F
- Low Odor
- Environmentally Friendly
- Indefinite Shelf Life
- Will Not Cause Hazardous Polymerization
- Low evaporation rate

Physical Properties-

Viscosity @ 25°C	N.D.
Appearance	Clear Liquid
Odor	Mild Sweet Odor
Specific Gravity @ 25°C	1.08
Flash Point	>200° F
Vapor Density (Air = 1)	N.D.

Limitations- Notice: Reacts violently with strong acids or bases.

Packaging-

- 55 Gallon Drums-Drum containers filled by weight, volume is closely approximate.
- 5 Gallon Pails

Shelf Life- One year, in original, unopened factory containers, under normal storage conditions of 55°F to 95°F.

Safety-

- Read Material Safety Data Sheet before using.
- Keep out of reach of children
- Wear safety glasses and neoprene gloves

Preparation and Installation- Dzolv should be used the same as any other solvent and cleaner. Employ baths where possible for stationary cleaning. May be applied by scrub and brush to polyurea coatings in order to prepare surface for delayed overcoating. Consult **VersaFlex**.

Technical Services-Sales and Customer Support (800) 870-8842

Warranty- **VersaFlex Incorporated** will refund the price of or replace, at its election, product it finds to be defective provided the product has been used properly. Except as expressly stated above, the Company makes no warranty of merchantability and no warranty of fitness for any particular purpose, nor does it make any warranty, expressed or implied, of any nature whatsoever with respect to the product or its use. In no event shall the company be liable for delay caused by defects, for loss of use, for indirect, special or consequential damages, or for any charges or expenses of any nature incurred without its written consent.